SS 15.5 - Smoke Separations

Address:						
Provided by (name):						
Register (Additional sheets may be required)						
	Location and Type Eg. gib ceiling, glass wall	Doo	rs, hold open devices etc	used	Features	
1						
2						
3						
4						
5						
6						
Installation Standard:		 □ NZBC C/AS1 □ Specifically Designed Alternative Solution □ Other (Historical) 				
Inspections & Maintenance Standard:		Compliance Schedule Handbook				
Standard.		Specifically designed solution provide details separately				
As a minimum these inspections and maintenance procedures will be carried out:		Planned preventative maintenance and responsive maintenance will be carried out in accordance with the nominated performance and inspection standard or document to ensure the system will operate as required. See below.				
Buildings Requiring daily maintenance: If ticked daily inspections are required as stated below (doors only)		CS Purpose group CL Purpose group CO Purpose group CM Purpose group Building undergoing Building Work affecting a Fire Separation Monthly and Annually for all other purpose groups				
	pection frequency and ponsibility:		Daily	Owner IQP		
			Monthly	Owner IQP		
			Six-monthly	Owner IQP		
			Annually	Owner IQP		
Inspections & Maintenance: Min. Maintenance and Testing as Specified in Compliance						

SS 15.5 - Smoke Separations

Schedule Handbook.		
Daily / Monthly Inspections		
Six Monthly and Annual inspections	 Smoke separations should be visually inspected for: Signs of damage or deterioration that could adversely affect their smoke control function, particularly with respect to closures, exposed smoke stopping and surface finish. New penetrations without suitable smoke stopping Doors forming part of an escape route to be checked and are not: locked barred blocked Door leaves or fire shutters close and latch automatically form any position Double acting doors and double leaf doors stop with the leaves in line with the frame, and seals (where fitted) are in contact at meeting stile and /or frame doors leaves on self closers shut with an acceptable maximum closing force (see code clause D1.3.4 (f)) Hardware is securely fixed No unauthorised hardware is attached Doors in exit ways can be opened without keys to allow ready egress from the building at all times Doors or windows are not kept open by methods other than hold open devices that comply with the building code and are in good working order 	
Donostios.	Doors haven't been relocated without suitable fire separation in the ceiling space The separation of all inspections are all inspections and a feet to be a separation of all inspections.	
Reporting:	 The owner must keep records of all inspections, maintenance and repairs undertaken in the previous 24 months. The records must be kept with the compliance schedule and as a minimum, include: Details of any inspection, test or preventative maintenance carried out. Include dates, work undertaken, faults found, remedies applied, and the person who performed the work. A Form 12A provided by an IQP annually 	

The information above is used to help generate the compliance schedule. If you are unsure of how to fill in this form please consult an IQP who is registered for the system above.