

COMPLIANCE SCHEDULE DETAILS: SS 14/2 - SIGNS FOR SPECIFIED SYSTEMS 1-13



PLEASE PROVIDE THE FOLLOWING INFORMATION

Date:

If you need help to complete this form, consult the system provider or an IQP who is registered for the system above.

Applicant name:	Building name:
Site address:	Classified Use
Existing Compliance Schedule Number(s): (if applicable)	Risk/purpose group:
	Fire hazard category:
	Total occupant load:

SPECIFIED SYSTEM DESCRIPTION (ADDRESS THOSE ITEMS THAT APPLY)

Specified systems:	Existing	New	Modified	Removed
Type:	Signs for one or more of the specified systems 1–13. SS 1 - Signs indicating max height at which goods may be stacked for sprinkler SS 2 – Sign instruction on how to operate a fire alarm call point SS 3 – Sign showing location of automatic door for accessibility SS 8 – Sign advising not to use the lift in the event of fire SS 8 – Sign indicating the lift’s rated load in persons and kilograms SS 8 – Sign showing location of lift for accessibility SS 12 – International symbol for deafness SS 13/2 Natural smoke control - operational signage for the ventilator Other SS and signage: [specify]			

Location plan for specified systems and records is attached: Yes No

No.	Equipment location	Make (main components)	Model
1			
2			
3			
4			
5			
6			
7			
8			

STANDARDS (ADDRESS THOSE ITEMS THAT APPLY)

Specifically designed solutions do not apply if the system has been installed against a specific Standard(s) / document.

Performance/
installation:

SS 1 - signs indicating max height at which goods may be stacked for sprinkler	
Performance standard(s):	
F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jan 2017. Amd 4. ss 2.0, 3.0 & para 5.4.	F8/AS1 Acceptable Solution for Clause F8 Signs. 14 Feb 2014. Amd 3. ss 2.0, 3.0 & para 5.4.
F8/AS1 Acceptable Solution for Clause F8 Signs. 10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & para 5.4.	F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Sep 1993. Amd 1. ss 1.0, 2.0 & para 6.4.2.
F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jul 1992. 1st Ed. ss 1.0, 2.0 & para 6.4.2.	NZS 4541 (Year)
SS 2 - sign instruction on how to operate a fire alarm call point	
Performance standard(s):	
NZS 4512:2010 Fire detection and alarm systems in buildings. Appendix E – Specification for manual call points.	NZS 4512:2003 Fire detection and alarm systems in buildings.
NZS 4512:1997 Fire alarm systems in buildings.	NZS 4512:1994 Fire alarm systems in buildings.
NZS 4512:1981 Automatic fire alarm systems in buildings.	NZS 4561:1973 Specification for manual fire alarm systems.
NZS 2211:1968 Manual fire alarm systems for use in buildings.	
and /or;	
F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jan 2017. Amd 4. ss 2.0, 3.0 & para 5.1.	F8/AS1 Acceptable Solution for Clause F8 Signs. 14 Feb 2014. Amd 3. ss 2.0, 3.0 & para 5.1.
F8/AS1 Acceptable Solution for Clause F8 Signs. 10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & para 5.1.	F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Sep 1993. Amd 1. ss 1.0, 2.0 & 4.1.
F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jul 1992. 1st Ed. ss 1.0, 2.0 & 4.1.	
SS 3 - sign showing location of automatic door for accessibility	
Performance standard(s):	
NZS 4121:2001 Design for Access and Mobility – Buildings and Associated Facilities. Appendix E – International symbols.	
NZS 4121:1985 Code of practice for design for access and use of buildings and facilities by disabled persons	
and /or;	
F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jan 2017. Amd 4. ss 2.0, 3.0 & 6.0.	F8/AS1 Acceptable Solution for Clause F8 Signs. 14 Feb 2014. Amd 3. ss 2.0, 3.0 & 6.0.
F8/AS1 Acceptable Solution for Clause F8 Signs. 10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & 6.0.	F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Sep 1993. Amd 1. ss 1.0, 2.0 & 5.0.
F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jul 1992. 1st Ed. ss 1.0, 2.0 & 5.0.	

STANDARDS (ADDRESS THOSE ITEMS THAT APPLY)

Specifically designed solutions do not apply if the system has been installed against a specific Standard(s) / document.

Performance/
installation:

SS 3/1 - sign showing location of remote switch for automatic door

Performance standard(s):

C/AS2 Acceptable Solution for Buildings other than Risk Group SH. 27 Oct 2019.

Amd 1. para 3.15.2.

And;

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jan 2017. Amd 4. ss 2.0, 3.0 & 4.0.

F8/AS1 Acceptable Solution for Clause F8 Signs.
10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & 4.0.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jul 1992. 1st Ed. ss 1.0, 2.0 & 3.0.

F8/AS1 Acceptable Solution for Clause F8 Signs.
14 Feb 2014. Amd 3. ss 2.0, 3.0 & 4.0.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Sep 1993. Amd 1. ss 1.0, 2.0 & 3.0.

SS 3/3 - Sign showing interfaced fire or smoke doors or windows that have an auto-closer

Performance standard(s):

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jan 2017. Amd 4. ss 2.0, 3.0 & 5.2.

F8/AS1 Acceptable Solution for Clause F8 Signs.
10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & 5.2

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jul 1992. 1st Ed. ss 1.0, 2.0 & 4.2.

F8/AS1 Acceptable Solution for Clause F8 Signs.
14 Feb 2014. Amd 3. ss 2.0, 3.0 & 5.2.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Sep 1993. Amd 1. ss 1.0, 2.0 & 4.2.

SS 6 - Sign showing location of fire hydrants in stairwells

Performance standard(s):

NZS 4510:2008 Fire hydrant systems for buildings.

NZS 4510:1978 Code of practice for riser mains for
fire service use

And;

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jan 2017. Amd 4. ss 2.0, 3.0 & 5.5.

F8/AS1 Acceptable Solution for Clause F8 Signs.
10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & 5.5.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jul 1992. 1st Ed. ss 1.0, 2.0 & para 6.4.3.

NZS 4510:1998 Fire hydrant systems for buildings

F8/AS1 Acceptable Solution for Clause F8 Signs.
14 Feb 2014. Amd 3. ss 2.0, 3.0 & 5.5.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Sep 1993. Amd 1. ss 1.0, 2.0 & para 6.4.3.

SS 8 - Sign advising not to use the lift in the event of fire

Performance standard(s):

NZS 4332:1997 Non-domestic passenger and goods
lifts. para 25.6.

And;

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jan 2017. Amd 4. ss 2.0, 3.0 & para 5.3.

F8/AS1 Acceptable Solution for Clause F8 Signs.
10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & para 5.3.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jul 1992. 1st Ed. ss 1.0, 2.0 & para 6.4.1.

NZS 4332:1994 Non-domestic passenger and
goods lifts.

F8/AS1 Acceptable Solution for Clause F8 Signs.
14 Feb 2014. Amd 3. ss 2.0, 3.0 & para 5.3.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Sep 1993. Amd 1. ss 1.0, 2.0 & para 6.4.1.

STANDARDS (ADDRESS THOSE ITEMS THAT APPLY)

Specifically designed solutions do not apply if the system has been installed against a specific Standard(s) / document.

Performance/
installation:

SS 8 - Sign indicating the lift's rated load in persons and kilograms

Performance standard(s):

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jan 2017. Amd 4. ss 2.0, 3.0 & para 7.3

F8/AS1 Acceptable Solution for Clause F8 Signs.
10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & para 7.3.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jul 1992. 1st Ed. Para. 1.0, 2.0 & para 6.3.2.

EN 81-20:2014 Safety rules for the construction and installation of lifts. Lifts for the transport of persons and goods. Passenger and goods passenger lifts; as modified by D2/AS1.

F8/AS1 Acceptable Solution for Clause F8 Signs.
14 Feb 2014. Amd 3. ss 2.0, 3.0 & para 7.3.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Sep 1993. Amd 1. ss 1.0, 2.0 & para 6.3.2.

NZS 4332:1997 Non-domestic passenger and goods lifts; as modified by D2/AS1.

SS 8 - Sign showing location of lift for accessibility

Performance standard(s):

NZS 4121:2001 Design for Access and Mobility – Buildings and Associated Facilities.
Appendix E – International symbols.

Or;

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jan 2017. Amd 4. ss 2.0, 3.0 & 6.0.

F8/AS1 Acceptable Solution for Clause F8 Signs.
10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & 6.0.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jul 1992. 1st Ed. ss 1.0, 2.0 & 5.0.

F8/AS1 Acceptable Solution for Clause F8 Signs.
14 Feb 2014. Amd 3. ss 2.0, 3.0 & 6.0.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Sep 1993. Amd 1. ss 1.0, 2.0 & 5.0.

SS 8 - Sign advising safety instructions for escalators and moving walks use

Performance standard(s):

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jan 2017. Amd 4. ss 2.0, 3.0 & 7.5.

F8/AS1 Acceptable Solution for Clause F8 Signs.
10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & 7.5.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jul 1992. 1st Ed. ss 1.0, 2.0 & 6.6.

F8/AS1 Acceptable Solution for Clause F8 Signs.
14 Feb 2014. Amd 3. ss 2.0, 3.0 & 7.5.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Sep 1993. Amd 1. ss 1.0, 2.0 & 6.6.

SS 12 - International symbol for deafness

Performance standard(s):

NZS 4121:2001 Design for Access and Mobility – Buildings and Associated Facilities.
Appendix E – International symbols.

NZS 4121:1985 Code of practice for design for access and use of buildings and facilities by disabled persons.

Or;

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jan 2017. Amd 4. ss 2.0, 3.0 & para 6.3.

F8/AS1 Acceptable Solution for Clause F8 Signs.
10 Apr 2012. 2nd Ed. ss 2.0, 3.0 & para 6.3.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Jul 1992. 1st Ed. ss 1.0, 2.0 & para 5.0.3.

F8/AS1 Acceptable Solution for Clause F8 Signs.
14 Feb 2014. Amd 3. ss 2.0, 3.0 & para 6.3.

F8/AS1 Acceptable Solution for Clause F8 Signs.
1 Sep 1993. Amd 1. ss 1.0, 2.0 & para 5.0.3.

STANDARDS (ADDRESS THOSE ITEMS THAT APPLY)

Specifically designed solutions do not apply if the system has been installed against a specific Standard(s) / document.

Performance/ installation:	<p>SS 13/2 – Natural smoke control - operational signage for the ventilator</p> <p>Performance standard(s):</p> <p>AS 1851:2012 - Routine service of fire protection systems and equipment</p>																				
Inspections:	<table border="0"> <tr> <td data-bbox="347 376 831 584"> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jan 2017. Amd 4.</p> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 10 Apr 2012. 2nd Ed.</p> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jul 1992. 1st Ed.</p> </td> <td data-bbox="963 376 1453 510"> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 14 Feb 2014. Amd 3.</p> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Sep 1993. Amd 1.</p> </td> </tr> <tr> <td colspan="2" data-bbox="963 539 1481 701"> <p>Signs shall be inspected regularly to ensure continued effectiveness. Inspections of signs required for emergency purposes to be illuminated shall be inspected monthly and annually. For other signs inspections shall be done annually.</p> </td> </tr> <tr> <td colspan="2" data-bbox="347 741 1142 763"> <p>Standard relating to one or more of the specified systems 1–13. List Standard(s):</p> </td> </tr> <tr> <td colspan="2" data-bbox="363 842 1474 1010"> <table border="0"> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> </table> </td> </tr> </table>	<p>F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jan 2017. Amd 4.</p> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 10 Apr 2012. 2nd Ed.</p> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jul 1992. 1st Ed.</p>	<p>F8/AS1 Acceptable Solution for Clause F8 Signs. 14 Feb 2014. Amd 3.</p> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Sep 1993. Amd 1.</p>	<p>Signs shall be inspected regularly to ensure continued effectiveness. Inspections of signs required for emergency purposes to be illuminated shall be inspected monthly and annually. For other signs inspections shall be done annually.</p>		<p>Standard relating to one or more of the specified systems 1–13. List Standard(s):</p>		<table border="0"> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> </table>		_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____
<p>F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jan 2017. Amd 4.</p> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 10 Apr 2012. 2nd Ed.</p> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Jul 1992. 1st Ed.</p>	<p>F8/AS1 Acceptable Solution for Clause F8 Signs. 14 Feb 2014. Amd 3.</p> <p>F8/AS1 Acceptable Solution for Clause F8 Signs. 1 Sep 1993. Amd 1.</p>																				
<p>Signs shall be inspected regularly to ensure continued effectiveness. Inspections of signs required for emergency purposes to be illuminated shall be inspected monthly and annually. For other signs inspections shall be done annually.</p>																					
<p>Standard relating to one or more of the specified systems 1–13. List Standard(s):</p>																					
<table border="0"> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> </table>		_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____								
_____	_____	_____	_____																		
_____	_____	_____	_____																		
_____	_____	_____	_____																		
Maintenance:	<p>Signs shall be:</p> <ul style="list-style-type: none"> • Replaced if not of the correct type • Replaced immediately should they be missing • Refurbished before they become illegible <p>Standard relating to one or more of the specified systems 1-13. List Standard(s):</p> <table border="0"> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> <tr> <td>_____</td> <td>_____</td> <td>_____</td> <td>_____</td> </tr> </table>	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____	_____								
_____	_____	_____	_____																		
_____	_____	_____	_____																		
_____	_____	_____	_____																		

INSPECTIONS, MAINTENANCE AND REPORTING (ADDRESS THOSE ITEMS THAT APPLY)

Minimum inspection and maintenance procedures:	<p>Regular inspection and responsive maintenance will be carried out in accordance with the nominated performance and inspection standard of the associated system, and to ensure signs remain correctly positioned and legible and, where appropriate, ensure the escape route is identified.</p>
Inspection frequency and responsibility:	<p>Depending on the type of installation and its performance standard/document:</p> <p>Specifically designed solutions: by IQP only</p> <p>Standard /other document:</p> <p>Daily by owner / representative (for Risk group CA / Purpose groups CS, CL, CO, CM)</p> <p>Monthly by owner</p> <p>Monthly by IQP only (for other Risk group / Purpose groups)</p> <p>Annually by IQP only</p>

INSPECTIONS, MAINTENANCE AND REPORTING (ADDRESS THOSE ITEMS THAT APPLY)

Inspections & Maintenance:

Monthly Inspections:

Illuminated signs will be inspected to ensure they are:

- The correct type
- Present and in the right locations
- Legible
- Performing as required e.g. illuminated signs are illuminating.

Annual Inspections:

Signs not required to be illuminated will be inspected to ensure they are:

- The correct type
- Present and in the right locations
- Legible

Signs required to be illuminated will be tested to ensure they:

- Remain illuminated in the event of a failure of the main lighting supply, for the same duration as required by Building Code Clause F6 Visibility in Escape Routes.

Specific considerations:

SS 12 Audio loops or other assistive listening systems

- Checks will be made to ensure the following signs or displays are present and in the right locations, where required.
- Approved international signage indicating audio loop availability is displayed at entrances to the venue, auditorium, room or area.
- A map or a display of the area covered by the audio loop, its location if coverage is limited within the venue, and directions to the indicated area are displayed
- Where counter loops are installed, each counter displays a sign indicating availability.
- The transmission channel used for the venue is displayed at the entrances to the venue to allow users to adjust their receivers to the frequency channel in use.

SS 13/2 Natural smoke control

- Checks will be made to ensure any operational signage for the ventilator is still in place and legible.

Reporting:

The owner will keep records of all inspections, maintenance and repairs undertaken in the previous 24 months. These will be recorded in the on-site log book or electronically, which will remain available with the most recent compliance schedule, and as a minimum include:

- Details of any inspection, test or preventative maintenance carried out, including dates, works undertaken, faults found, remedies applied and the person who performed the work.
- Form 12A provided annually by the IQP.